



The "MASTER INOX" series do not require cathodic protection in normal conditions of use with drinking water (European Directive 98/83/CE). However, depending on the installation site, drinking water conditions may differ greatly from the drinking water requirements established by current regulations. In this case, and taking as the reference a 150 mg/l chloride content limit, we recommend fitting a permanent, maintenance-free "lapesa correx-up" cathodic protection system in the storage tank.

"lapesa correx-up"
permanent cathodic
protection system:

Totally automatic!

Maintenance free!



KIT C.P. lapesa correx-up	Applicable to MASTER INOX tanks models:
KITPCTIMX2A	MXV1500RB...3000RB
	MXV1500SB/SSB/EB
	MXV3000RB...5000RB
KITPCTIMX3A	MXV2000SB/SSB/EB...2500SB/SSB/EB
KITPCTIMX4A	MXV3000SB/SSB/EB...4000SB/SSB/EB
KITPCTIMX5A	MXV5000SB/SSB/EB

"lapesa correx-up" permanent cathodic protection system: Maintenance-free permanent cathodic protection unit. These anodes do not wear out and they emit the necessary electric current automatically, providing the tank with cathodic protection via an individual potentiostat for each anode, connected to the mains electricity.



ACCESSORIES - MASTER INOX



EXTERNAL LINING

External lining for "MASTER INOX" tanks with top cover, ND400 side manhole cover and trims for hydraulic connections. Standard external lining: GREY / RAL 7042.

Capacity (l)	Standard (KIT reference)	Fireproof (KIT reference)	Weatherproof (KIT reference)
1500	FME1500	FME1500	FME1500/EX
2000	FME2000	FME2000	FME2000/EX
2500	FME2500	FME2500	FME2500/EX
3000	FME3000	FME3000	FME3000/EX
3500	FME3500	FME3500	FME3500/EX
4000	FME4000	FME4000	FME4000/EX
5000	FME5000	FME5000	FME5000/EX
6000	FME6000	FME6000	FME6000/EX

ALUNOX EXTERNAL LINING

External aluminium sheet lining. ALUNOX external lining is supplied ready-mounted on the tank, over the PU insulation.

Capacity (l)	Aluminium lining ALUNOX - Ref.
1500	FME1500/ALUNOX-B
2000	FME2000/ALUNOX-B
2500	FME2500/ALUNOX-B
3000	FME3000/ALUNOX-B
3500	FME3500/ALUNOX-B
4000	FME4000/ALUNOX-B
5000	FME5000/ALUNOX-B

